



PASTELLI

Pastel, noble soul.

Pastelli is the most original mosaic element, it is the code our time, the link between an emotional connection between our identity and the soul of the world.

The architecture of colour.

Enduring yet subtle in appearance - this is the nature of Pastelli, fashioned to bring the architecture of living spaces alive.

Pastelli is the ideal solution for floors, where the distinction between interiors and exteriors, between flooring and covering, becomes more seamless.

A remarkable porcelain stoneware, a full-body, coloured and pressed stoneware, with antibacterial, antifungal, anti-stain properties and almost zero moisture absorption rates.

Pastelli is available in 8 colours and 3 sizes, with the possibility of using contrasting joints to create distinct forms and decorative lines inside the single mesh sheet. For a project that is aspiring and flexible. Where details and design are translated into the context of the geometric textures in connection with shapes, colours and settings.





Mosaic

- o Module 300 x 300 mm (sheet size)
- o 25 x 25 mm
- o Ostrica PST 7003


Floor


Mosaic


- o Module 300 x 300 mm (sheet size)
- o 25 x 25 mm
- o Ostrica PST 7003

False ceiling


- Module 300 x 300 mm (sheet size)12.5 x 37.5 mm
- o Osso PST 3001



















Mosaic


- o Module 300 x 300 mm (sheet size)
- o 25 x 25 mm
- o Aurora PST 7004

Тор


- o Module 300 x 300 mm (sheet size)
- o 12.5 x 12.5 mm
- o Nocciola PST 4006








aurora



nocciola








Mosaic

- Module 300 x 300 mm (sheet size)25 x 25 mm
- o Conchiglia PST 7005


Floor


- o Module 300 x 300 mm (sheet size)
- o 25 x 25 mm
- o Conchiglia PST 7005











Mosaic

- o Module 300 x 300 mm (sheet size)
- o 12.5 x 12.5 mm
- o Nocciola PST 4006


Floor


Mosaic

- o Module 300 x 300 mm (sheet size)
- o 12.5 x 12.5 mm
- o Osso PST 4001


Bench, niche & bathtub

- o Module 300 x 300 mm (sheet size)
- o 12.5 x 12.5 mm
- o Osso PST 4001






nocciola



osso






Wall & Columns

Mosaic

- o Module 300 x 300 mm (sheet size)
- o 12.5 x 12.5 mm
- o Osso PST 4001

Floor

- Module 300 x 300 mm (sheet size)12.5 x 12.5 mm
- o Ruscello PST 4007




ruscello













Mosaic

- Module 300 x 300 mm (sheet size)12.5 x 37.5 mm
- o Ruscello PST 3007


Floor

- Module 300 x 300 mm (sheet size)
 1.25 x 1.25 mm
- o Ruscello PST 4007










ruscello









- Module 300 x 300 mm (sheet size)
 12.5 x 37.5 mm
 Antracite PST 3008

- o Cenere PST 3002






antracite



cenere









COLOURS

MOSAIC SIZE 12.5X37.5 MM






sheet size 300 x 300 mm (net mounted)


mosaic size 12 x 12 mm | 25X25 mm | 12.5x37.5 mm

abrasion coefficient:

(PEI) V OSSO | CENERE | OSTRICA | AURORA | CONCHIGLIA | NOCCIOLA | RUSCELLO | ANTRACITE

application






WALLS




INDOOR

OUTDOOR

FLOORS






Mosaic


- o Module 300 x 300 mm (sheet size)
- o 12.5 X 12.5 mm
- o 12.5 x 37.5 mm
- o 25 x 25 mm
- o Osso PST 4001 PST 3001 PST 7001


Floor

- o Module 300 x 300 mm (sheet size)
- o 12.5 X 12.5 mm
- o 12.5 x 37.5 mm
- o 25 x 25 mm
- o Osso PST 4001 PST 3001 PST 7001













- o Module 300 x 300 mm (sheet size)
- o 12.5 x 37.5 mm
- Conchiglia PST 3005Osso PST 3001












- o Module 300 x 300 mm (sheet size)
- o 12.5 X 12.5 mm
- o 12.5 x 37.5 mm
- o 25 x 25 mm
- Conchiglia PST 3005Osso PST 7001
- o Nocciola PST 4006










BLEND A 600X600 mm





12.5x37.5 mm mosaic

300x300 mm sheet

colour: AURORA grout colour: CILIEGIA

BLEND B 600X600 mm





12.5x37.5 mm mosaic


12.5x37.5 mm mosaic


12.5x37.5 mm mosaic

300x300 mm sheet

colours: CONCHIGLIA | OSSO | NOCCIOLA grout colour: ANTRACITE

BLEND C 600X600 mm







12.5x37.5 mm mosaic

300x300 mm sheet

colour: RUSCELLO | ANTRACITE grout colour: ANTRACITE

BLEND D 600X600 mm






12.5x37.5 mm mosaic

300x300 mm sheet

colours: CONCHIGLIA | OSSO grout colour: CARAMEL




BLEND E 600X600 mm




12.5x37.5 mm mosaic 12.5x37.5 mm mosaic 12.5x37.5 mm mosaic 300x300 mm sheet

colour: AURORA grout colour: CILIEGIA

BLEND F 600X600 mm







12.5x37.5 mm mosaic

300x300 mm sheet

colours: RUSCELLO| NOCCIOLA grout colour: ANTRACITE

BLEND G 600X600 mm







300x300 mm sheet

colour: AURORA | ANTRACITE grout colour: MANHATTANE

BLEND H 600X600 mm





300x300 mm sheet

colours: OSTRICA | AURORA grout colour: GRIGIO CASTELLO



Pastelli is a full coloured body stoneware. This mosaic guarantees advanced technical performance that will not change over time. High firing temperatures and high compactness allow significant resistance to loads, shocks, wear and frost. With its low water absorption (E≤0.5%) this mosaic is the most suitable ceramic material for outdoor laying on floors and walls, including near surfaces that are damp or in contact with water. In particular, the Pastelli collection is a full-body coloured product, which starts from clay and pigmented earths which are then pressed, to compose each single tile in the different colour lines. A product that is perfectly coherent with other collections, for aesthetic potential and uncompromising durability.

It is possible to use the custom layouts in the catalogue to freely change the colours and obtain new colour combinations or design the desired laying scheme with the available formats, the template of which is created using a 3D printer

Installation in areas with underfloor heating

Installation in areas with underfloor heating Pastelli is suitable for underfloor heating systems, complying with the following requirements: - reduced thickness (7,2 mm) - good thermal conductivity of the ceramic material - minimum amount of glue required for laying - use of cement-based grouts for filling. Following these requirements will ensure the effective technical performance of the system, ensuring the optimal passage of heat and maintaining an ideal temperature in the room, while making the floor comfortable to the touch.



Antibacterial Defense Bio Shield+

Bio Shield+ antibacterial defense This collection is developed with Bioshield+, the first and only "native" bactericidal, anti-mould and anti-stain treatment, which is long-lasting and protects the surface in any condition of use, temperature and light. Bioshield+ was born from the collaboration with Metco Italia, a leader in research in this sector and the creator of the innovative Zerobakter 4ever finish. This solution (which is much more than just an "antibacterial shield") is certified according to the strictest international standards, guaranteeing constant protection, which is resistant to the chemical agents present in the most common detergents, but does not interfere with the aesthetic and technical properties of the ceramic surface. It is therefore ideal for settings where maximum hygiene and comfort must be guaranteed, such as in hospitals, schools, canteens, wellness environments, hotels, and our homes.

Ultra technical and Ultra Green

Ultra technical and Ultra Green Spotless, literally. This is Pastelli, an ultra-technical product that fits perfectly, focused on small format, aesthetic enhancement and attention to detail. A superior product from every point of view, anti-stain and antifungal, made in singlepressing. It is also a sustainable product, with certified earths and pigments, a factory sustainability balance, constant investments to improve machine and process efficiency.





porcelain stoneware



anti-slip



impact resistant



frost resistant



thermal shock resistant



bending strength



stain resistant



low water absorption ($E \le 0.5\%$)



bacteriostatic and bacterial finish containing silver nanoparticles



fungicidal efficacy on the germination of fungi and molds harmful to humans











ISO: PASTELLI

PORCELAIN STONEWARE

		standard	tolerances	results
	sides 298.4X298.4 mm	EN ISO 10545-2	± 0.5.%	± 0.2.%
	thickness 7.2 mm	EN ISO 10545-2	± 5%	± 4.%
SURFACE DIMENSIONS &	straightness of edges	EN ISO 10545-2	± 0.5%	± 0.4%
UNI EN ISO 16545/2 QUALITIES	squareness	EN ISO 10545-2	<u>+</u> 0.6%	± 0.4%
	surface qualities	EN ISO 10545-2	< 95%	< 95%
	surface flatness	EN ISO 10545-2	± 0.5%	± 0.4%



ISO: PASTELLI

PORCELAIN STONEWARE

physical properties	standard	requirements	results
WATER ABSORPTION	ISO 10545-3	E ≤ 0.5% appendix G	≤ 0.5%
BREAKING STRENGTH IN N	ISO 10545-4	700 min. appendix H	> 1800
FLEX RESISTANCE	ISO 10545-4	30 min. appendix G	> 50 N/mm ²
IMPACT RESISTANCE	ISO 10545-5	testing method available	> 0.6 (appendix P)
ABRASION RESISTANCE	ISO 10545-7	indicated by producer	PEI V
COEFFICIENT OF THERMAL LINEAR EXPANSION	ISO 10545-8	testing method available	< 7·10-6/°C
THERMAL SHOCK RESISTANCE	ISO 10545-9	testing method available	guaranteed
MOISTURE EXPANSION	ISO 10545-10	testing method available	< 0.04%
CRAZING RESISTANCE	ISO 10545-11	required	guaranteed
FROST RESISTANCE	ISO 10545-12	required	guaranteed



†ECHNICAL CHARACTERISTICS

PORCELAIN STONEWARE

chemical properties	standard	requirements	results
	EN ISO 10545-13		
CHEMICAL RESISTANCE	resistance to chemical products for housekeeping & to the additives used in swimming pools	B min	A
ISO 10545-13	resistance to diluted acid & alkali solutions	indicated by producer	LA
	resistance to highly concentrated acid & alkali solutions	testing method available	HA
FIRE RESISTANCE		decision 96/603/CE	class A1
STAIN RESISTANCE	EN ISO 10545-14	class 3 min.	3 min.
Pb Cd LEAD & CADIUM DISCHARGE	EN ISO 10545-15	testing method available	on request
RESISTANCE OF COLOURS TO SUNLIGHT	DIN 51094	not envisaged	guaranteed

	standard	nominal shape	classification group
		125 x 125 mm	R10
ASSESSMENT OF SLIP RESISTANCE	DIN 51130	125 x 375 mm	R10
		250 x 250 mm	R10
	DIN 51097	125 x 125 mm	В
		125 x 375 mm	В
		250 x 250 mm	В

Unglazed ceramic tiles, dry pressed with low water absorption. E ≤ 0,5% - gruppo B I a - M - UGL - EN 14411 appendice G



ASTM: PASTELLI

PORCELAIN STONEWARE

physical properties	standard	requirements	results
WATER ABSORPTION	ASTM C373	wa ≤ 0.5%	< 0.5% class P1
BREAKING STRENGTH IN Ibf	ASTM C648	≥ 250 lbf	≥ 250 lbf
THERMAL SHOCK RESISTANCE	ASTM C484	testing method available	guaranteed
CRAZING RESISTANCE	ASTM C242	required	guaranteed
FROST RESISTANCE	ASTM C1026	required	guaranteed



ASTM: PASTELLI

PORCELAIN STONEWARE

chemical properties	standard	requirements	results
CHEMICAL RESISTANCE	ASTM C650	indicated by producer	guaranteed
STAIN RESISTANCE	ASTM C1378	required	guaranteed

ASSESSMENT OF SLIP RESISTANCE	test method	PST test	requisites	results
	ANSI A137.1	12 x 12 mm (DCOF)	DCOF > 0.42	0.6
		25 x 25 mm (DCOF)	DCOF > 0.42	0.67
		12 x 37.5 mm (DCOF)	DCOF > 0.42	0.78

ANTIBACTERIAL TEST (calculation of antibacterial activity expresses as a percentage)

chemical properties	standard	reduction%	
	ISO 22196:2011	97.90%	
ANTIBACTERIAL PERFORMANCE	ASTM E3031-2015	99.98%	





Stonegres Limited
20-22 Wenlock Road
London
N1 7GU
tel: 020 8943 3154
info@stonegres.co.uk | www.stonegres.co.uk